

SECTION A - A

OPERATING WHEEL
MATERIAL : CAST IRON

MOUNTING PLATE & SPINDLE
MATERIAL : MILD STEEL
DRESS WELD FLUSH ON REAR FACE.


REFERENCE DRAWINGS

SYDNEY CBD SUBSTATIONS EMERGENCY PULL-OUT GEAR OPERATING EQUIPMENT ARRGT & DETAILS B1-16500
 SYDNEY CBD SUBSTATIONS EMERGENCY PULL-OUT GEAR OPERATING EQUIPMENT ARRANGEMENT B1-18894

NOTES

- ALLOWANCE OF ADDITIONAL MATERIAL TO BE MADE FOR MACHINING OF BOTH ENDS & BORE OF BOSS AFTER CASTING.
- ENDS OF STAINLESS STEEL WIRE ROPE TO PASS THROUGH DRILLED HOLES PROVIDED & SECURED AROUND M10 SET SCREWS & WASHERS.
- MOUNTING PLATE TO BE THOROUGHLY CLEANED THEN GIVEN ONE COAT OF ZINC CHROMATE PRIMER FOLLOWED BY TWO COATS OF GREY ENAMEL. SPINDLE TO BE LEFT UNPAINTED.
- SPINDLE & BORE OF PULLEY TO BE GREASED UPON ASSEMBLY.
- REFER TO DRAWING B1-18894 FOR GENERAL ARRANGEMENT.

| | |
|---|----------------------------|
| CAD DRAWING DO NOT MANUALLY AMEND | |
| AMENDMENTS | |
| 2. DRAWING METRICATED & REDRAWN ON CAD. REF DRG & STANDARD NOTES ADDED. | |
| C. SAWDY CHECKED | 10-07-2003 P.H |
| 3. NEW AUSGRID BORDER & LOGO ADDED. | |
| R. LAALAA CHECKED | 10-09-2013 T.L. |
| 4. BORDER & TITLE BLOCK UPDATED. | |
| M.BENNETT CHECKED: | 20/09/2024 L.MARTINUZZI |
| APPROVED: | M.BENNETT |



Ausgrid
 24-28 Campbell Street
 SYDNEY NSW 2000

| | |
|----------------|---------------|
| ISSUED FOR | CONSTRUCTION |
| PROJECT NUMBER | ES 99-15-4-14 |

| | |
|----------|------------|
| SCALE | 1:2 |
| DESIGNED | - |
| DRAWN | C.SAWDY |
| CHECKED | G.ANTONIOU |
| APPROVED | P.HUDSON |
| DATE | 10/07/2003 |
| TRIM REF | - |

| | | | |
|--|------------|-------|-----|
| SYDNEY CBD TYPE SUBSTATIONS & CONTROL POINTS ISOLATING SWITCH OPERATING WHEEL FOR PULL-OUT GEAR ARRANGEMENT & DETAILS | | | |
| SIZE | DRAWING No | SHEET | AMD |
| A2 | 10578 | 1 | 4 |