

7		8		
TAINED FROM THE PROJEC [®] INTS. AD EARTH WIRE SIZE. NTS. E TO BE CONSTRUCTED ON) BE	А
E TO BE CONSTRUCTED ON THIS ARRANGEMENT IS TO BE				
UITS ON A 33kV STRUCTURE, THE POSSIBLE USE OF LIVE 3E CONSIDERED WHEN NOMINATING THE CIRCUIT 3LEARANCE OF 2500mm IF REQUIRED. AND DRESSED ON SITE DRILLING AND SCARFING TO BE ATIVES. ER ARE TO BE COATED WITH GRAPHITE GREASE. E STAYWIRE CLEARANCE FROM THE PHASE CONDUCTORS QUIREMENTS. OR OPTION IS SHOWN ON THIS CONSTRUCTION DRAWING. LLED ON POLES WHERE ACCESS FOR NORMAL MAINTENANCE OR THE LIFE OF THE POLE. IF POLE STEPS ARE INSTALLED,			В	
OR THE LIFE OF THE POLE. I QUIREMENTS OF NETWORK {			LLED,	
				С
				D
		250144	A/R	
NTING & BONDING, ARRANGEMENT	-4 (SEE NOTE 7)			
NDING, ARRANGEMENT -1b (SEE NOTE 7)		514161	- 3	
		508726	1	E
		513988	1	
		DRG. No	QTY	
CONSTRUCTION		•	•	
CAL DELTA				
LINE POST				
CONSTRUCTION				F
		SHEET	AMD	
238364		01	1	
7		8		\bigcirc