



19	WASHER - SPRING, M12, GALVANISED	518082	H12047	3
18	BOLT & NUT - M12x25mm, HEX., GALVANISED	515466	46359	3
17	STRAP - TIEDOWN, CABLE, BLACK, 293x4.8mm, UV STABILISED		H5018	3
16	BRACKET - POLE MOUNTING FOR 33kV POLYMERIC SURGE ARRESTER	527144	H113456	3
15	STAPLE - FENCING, 3.15x25mm, GALVANISED		175601	A/R
14	BRACKET - SHEATH VOLTAGE LIMITER & CABLE SUPPORT	527024	H113431	3
13	LIMITER - SHEATH VOLTAGE (BOWTHORPE HEA 6) (SEE NOTES 4 & 5)			3
12	CONDUCTOR - OVERHEAD, TAPPING			A/R
11	CABLE - UNDERGROUND			A/R
10	CABLE - COPPER, 19/1.53 (35mm ²), PVC INSULATED, H.D.		H13629	A/R
9	CLAMP - SPLIT BOLT, B24, TINNED		H18776	2
8	LUG - COMPRESSION, COPPER, 19/1.53 (35mm ²), M12 HOLE	514053	H20501	13
7	SCREW - COACH, M12x65mm, GALVANISED		H40476	A/R
6	ARRESTER - SURGE, 33kV, 10kA, HEAVY DUTY, STATION CLASS 2, POLYMER		H113407	3
5	LUG - BI-METAL, COMPRESSION TO SUIT O/H CONDUCTOR	514053		3
4	LUG - COPPER, COMPRESSION, WATER BLOCKED TO SUIT U/G CABLE			3
3	WASHER - FLAT, M12, GALVANISED	518081	177982	A/R
2	SADDLE - POLE, GALVANISED, RADIUS TO SUIT U/G CABLE (MOUNTED AT MAXIMUM 1.5m INTERVALS)	513972		A/R
1	TERMINATION - KIT, HEATSHRINK, 33kV OUTDOOR TO SUIT U/G CABLE			3
ITEM	DESCRIPTION	DRG. No.	STOCK CODE	QTY

SUPERSEDED

ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE

CAD DRAWING
DO NOT MANUALLY AMEND
A M E N D M E N T S
DWN: PATRICIA RIOS
CHKD: PHILLIP JONES
DATE: 09/04/2019
SUPERSEDED BY
DRGS : 238370 & 248461.
6

APP'D by: GLENN FORD



DESIGN & ENGINEERING BRANCH
145 NEWCASTLE RD WALLSEND, NSW 2287
Ph 02 4951 9388
Fax 02 4951 9389

SCALE	1:25
DESIGNED	-
DRAWN	M.A.
CHECKED	P.S.
APPROVED	I NICHOLS
DATE	02/09/93
PROJECT NUMBER	STD
PROJTRAK NUMBER	

STANDARD CONSTRUCTION			
33kV POLE HEATSHRINK TERMINATION			
FOR 3 SINGLE CORE CABLES			
SINGLE POINT BONDED SYSTEM			
4-130			
SIZE	DRAWING No	SHEET	AMD
A3	527025	01	6